

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: KB 3342

Chemical Formula: Not Applicable

CAS Number: Proprietary Blend

Synonyms: None

General Use: Various

Manufacturer: KMCO, LP, 16503 Ramsey Road, Crosby, Texas, 77532, Phone (281)328-3501, Fax(281)328-9528

24-HOUR EMERGENCY NUMBER: CHEMTREC 1-800-424-9300

Section 2 - Composition / Information on Hazardous Ingredients

Ingredient Name	CAS Number	% wt <i>or</i> % vol
Xylene	1330-20-7	32 - 36
Ethyl benzene	100-41-4	3 - 4

Trace Impurities:

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Xylene	100 ppm 435 mg/m ³	none estab.	100 ppm 434 mg/m ³	150 ppm 651 mg/m ³	100 ppm 435 mg/m ³	150 ppm 655 mg/m ³	900 ppm
Ethyl benzene	100 ppm 435 mg/m ³	none estab.	100 ppm 434 mg/m ³	125 ppm 543 mg/m ³	100 ppm 435mg/ m ³	125 ppm 545 mg/m ³	800 ppm

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

DANGER! HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL, AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES SEVERE EYE IRRITATION. CAUSES IRRITATION TO SKIN AND RESPIRATORY TRACT. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CHRONIC EXPOSURE CAN CAUSE ADVERSE LIVER, KIDNEY, AND BLOOD EFFECTS. FLAMMABLE LIQUID AND VAPOR.

HMIS	
H	2
F	3
R	0

Potential Health Effects

Acute Effects

Inhalation: Inhalation of vapors may be irritating to the nose and throat. Inhalation of high concentrations may result in nausea, vomiting, headache, ringing in the ears, and severe breathing difficulties which may be delayed in onset. Substernal pain, cough, and hoarseness are also reported. High vapor concentrations are anesthetic and are central nervous system depressants.

Eye: Vapors cause eye irritation. Splashes cause severe irritation, possible corneal burns and eye damage.

Skin: Skin contact results in loss of natural oils and often results in a characteristic dermatitis. May be absorbed through the skin.

Ingestion: Ingestion causes burning sensation in mouth and stomach, nausea, vomiting and salivation. Minute amounts aspirated into the lungs can produce a severe hemorrhagic pneumonitis with severe pulmonary injury or death.

Carcinogenicity: IARC, NTP, and OSHA do not list product, xylenes, or ethyl benzene as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney, blood, or respiratory function may be more susceptible to the effects of this product.

Chronic Effects: Chronic inhalation can cause headache, loss of appetite, nervousness and pale skin. Repeated or prolonged skin contact may cause a skin rash. Repeated exposure of the eyes to high concentrations of vapor may cause reversible eye damage. Repeated exposure can damage bone marrow, causing low blood cell count. May damage the liver and kidneys.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Dispose of contaminated clothing in accordance with all local, state, and Federal regulations.

Ingestion: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspirations into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: 95°F (35°C)

Flash Point Method: PMCC

Burning Rate: Not Available

Autoignition Temperature: 867 °F (464 °C) data for xylene

LEL: 1.0 % v/v (data for xylene)

UEL: 7.0% v/v (data for xylene)

Flammability Classification: Flammable liquid and vapor

Extinguishing Media: Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak, and disperse vapors.

Unusual Fire or Explosion Hazards: Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Contact with strong oxidizers may cause fire. Sealed containers may rupture when heated. Sensitive to static discharge.

Hazardous Combustion Products: Carbon monoxide and unidentified organic compounds.

Fire-Fighting Instructions: Do not use direct water stream to extinguish fires. Product may travel with water and reignite. Vapors can flow along surfaces to distant ignition source and flash back. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode. Wear full protective clothing.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Use non-sparking tools and equipment. Do not flush to sewer.

Small Spills: Contain and recover liquid when possible. Collect liquid in an appropriate container or absorb with an inert material (e.g. vermiculite, dry sand), and place in a chemical waste container. Do not use combustible materials, such as saw dust.

Large Spills

Containment: Wear respirator and protective clothing as appropriate. Shut off source of leak if safe to do so. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Cleanup: Contain and recover liquid when possible. Collect liquid in appropriate container. Absorb residue with an inert material. Consult with your environmental department for detailed clean up instructions.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120). CERCLA requires reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

Section 7 - Handling and Storage

Handling Precautions: Protect against physical damage. Containers should be bonded and grounded for transfers to avoid static sparks. Use non-sparking type tools and equipment, including explosion proof ventilation. Do not attempt to clean empty containers.

Storage Requirements: Store out of direct sunlight in a cool, well ventilated area. Separate from incompatibles. Outside or detached storage is preferred.

Regulatory Requirements: This product contains the following chemical(s) subject to the reporting requirements of SARA Title III Section 311, 312, and 313: Xylene, Ethylbenzene.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid	Water Solubility: Insoluble
Appearance and Odor: Amber liquid with aromatic odor	Other Solubilities: Xylene: soluble Isopropanol: soluble
Odor Threshold: not available	Boiling Point: not determined
Vapor Pressure: not determined. [for xylene: 8 mm Hg at 68 °F (20 °C)]	Freezing/Melting Point: < -20° F
Vapor Density (Air=1): >1.0	Viscosity: not available
Formula Weight: not applicable	Refractive Index: not available
Specific Gravity (H₂O=1, at 4 °C): 0.985	Surface Tension: not available
pH: 5.0 – 8.0	% Volatile: not available
	Evaporation Rate: 0.4 (Butyl Acetate = 1)

Section 10 - Stability and Reactivity

Stability: Product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents.

Conditions to Avoid: Heat, flames, ignition sources and incompatibles.

Hazardous Decomposition Products: Thermal oxidative decomposition of product can produce carbon monoxide and unidentified organic compounds.

Section 11- Toxicological Information

	Toxicity Data: *
Eye Effects: Vapors cause eye irritation. Splashes cause severe irritation, possible corneal burns and eye damage.	Acute Inhalation Effects: Rat, LC50 (xylene): 5000 ppm / 4H
Skin Effects: Skin contact results in loss of natural oils and often results in a characteristic dermatitis. May be absorbed through the skin.	Acute Oral Effects: Rat, oral, LD50 (xylene): 4300 mg/kg Rat, oral, LD50 (ethyl benzene): 3500 mg/kg
	Chronic Effects: Repeated exposure can damage bone marrow and may damage the liver and kidneys.
	Carcinogenicity: Not Classifiable as to Human Carcinogenicity
	Teratogenicity: May cause teratogenic effects.

* See NIOSH, *RTECS*, for additional toxicity data.

Section 12 - Ecological Information

Ecotoxicity: For xylene: This material is expected to be slightly toxic to aquatic life. The LC50/96-hour values for fish are between 10 and 100 mg/L.

Environmental Fate: For xylene: When released into the soil, this material may evaporate to a moderate extent. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the water, this material may evaporate to a moderated extent.

Environmental Degradation: This material is not expected to bioaccumulate.

Section 13 - Disposal Considerations

Whatever cannot be saved for recovery or recycling should be disposed of in an approved waste facility, in accordance with Federal, State/Provincial and Local requirements. May be a RCRA hazardous waste due to the ignitability characteristic.

Section 14 - Transport Information**DOT Transportation Data (49 CFR 172.101):****Shipping Name:**

Flammable Liquid, n.o.s.
(contains xylenes, ethyl
benzene)

Hazard Class: 3**ID No.:** UN 1993**Packing Group:** III**Label:** 3, Flammable Liquid**Special Provisions**

(172.102): none

Packaging Authorizations**a) Exceptions:** 173150**b) Non-bulk Packaging:**
173.203**c) Bulk Packaging:** 173.242**Quantity Limitations****a) Passenger, Aircraft, or Railcar:**
60L**b) Cargo Aircraft Only:** 220L**Vessel Stowage Requirements****a) Vessel Stowage:** Location A**Section 15 - Regulatory Information****EU REACH - NOT REGISTERED AND CANNOT BE EXPORTED INTO THE EU.****EPA Regulations:**

RCRA Hazardous Waste Number (40 CFR 261.33): U239 (contains xylenes)

RCRA Hazardous Waste Classification (40 CFR 261): Ignitable (contains xylenes)

CERCLA Hazardous Substance (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4);
CWA, Sec. 307(a), CAA, Sec. 112 (contains xylenes, ethylbenzene)

CERCLA Reportable Quantity (RQ) (40 CFR 302.4): Xylene, 100 lbs; Ethylbenzene, 1000 lbs.

SARA 311/312 (40 CFR 370) Codes: Acute Health, Chronic Health, Fire Hazard (1,3,4) [contains xylenes]

SARA 313 Toxic Chemical (40 CFR 372.65): Listed effective 1/1/87 (xylenes)

SARA 304 EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1): Xylene 100 ppm, Ethylbenzene 100 ppm

OSHA Specifically Regulated Substance (29CFR 1910): Not listed

California Proposition 65 ingredients:

Ethylbenzene

Section 16 - Other Information**Prepared By:** KMCO, LP**Revision Notes:** All sections revised as part of conversion to 16 Section format.**Additional Hazard Rating Systems:** none.

Disclaimer: KMCO, LP believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. No warranty of fitness for any particular purpose, warranty of merchantability, or any other warranty expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and of the information referred to herein are beyond the control of KMCO, LP, KMOC, LP expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

For additional product information, please contact the KMCO, LP Sales Office at (281) 272-4100